



TYPICAL SUBMITTAL DATA

MODEL: 361PSL1611 / 361CSL1611
 BASE MODEL: 361PSL1611

Winding WC-1611

Voltage at -pf	Class B		Class F				Class H		
	80° C Ⓞ Continuous	90° C Ⓞ Lloyds	95° C Ⓞ ABS	105° C British Standard	105° C Continuous	130° C Ⓞ Standby	125° C British Standard	125° C Continuous	150° C Ⓞ Standby
240-1	40 (40)	40 (40)	40 (40)	40 (40)	40 (40)	40 (40)	40 (40)	40 (40)	45 (45)
240-.8	22 (28)	24 (30)	24 (30)	26 (33)	26 (33)	30 (38)	29 (36)	30 (38)	32 (40)

① Rise by resistance method, Mil-Std-705, Method 680.1b.

British Standard Rating per BS 5000

Submittal Data: 240 Volts*, 35.2 kW, 44 kVA, 0.8 P.F., 1800 RPM, 60 Hz, 1 Phase

Mil-Std-705B			Mil-Std-705B		
Method	Description	Value	Method	Description	Value
301.1b	Insulation Resistance	>1.5 Meg	505.3b	Overspeed	2250 RPM
302.1a	High Potential Test		601.4a	L-L Harmonic Maximum - Total (Distortion Factor)	5.0%
	Main Stator	1500 Volts	601.4a	L-L Harmonic Maximum - Single	5.0%
	Main Rotor	1500 Volts	601.1c	Deviation Factor	6.0%
	Exciter Stator	1500 Volts	--	Type	MAGNAPLUS
	Exciter Rotor	1500 Volts	--	Insulation	Class H
401.1a	Stator resistance - Line to Line		--	Coupling - Single Bearing	Flexible
	Dedicated connection	0.0695 Ohms	--	Amortisseur Windings	Full
	Rotor Resistance	0.75 Ohms	--	Exciter	Rotating
	Exciter Stator	23 Ohms	--	Voltage Regulator	SE350
	Exciter Rotor	0.135 Ohms	--	Voltage Regulation	1.00%
410.1a	No Load Exciter Field Amps at 240 Volts Line to Line	0.76 A DC	--	Cooling Air Volume	700 CFM

