




KATOLIGHT

STANDARD 45 SERIES



STANDARD EQUIPMENT


Voltmeter — 3½" 2% Accuracy
 Ammeter — 3½" 2% Accuracy
 Frequency Meter — 3½" 58-62 Hz Reed
 Combination Volt/Ammeter Selector Switch
 — 4 Position 3 Phase
 or Ammeter (only) — 3 Position 1 Phase
 Engine Gauges —
 Charge Rate Ammeter
 Water Temperature
 Oil Pressure
 Running Time Meter

Vibration / Shock Mounts (4)
 Engine Control — KASSEC, 12 or 24 volt DC with
 cyclic cranking timer, 4 engine shutdowns with four
 failure lights (overcrank, overspeed, low oil pressure
 and high engine temperature), 3 position mode
 switch (auto-off-manual). Engine control is designed
 for switch grounding on failure.

The Katolight Standard 45 Series Control Panel is a complete package, ready for installation. The panels have been designed and tested to insure a reliable quality product, a Katolight tradition. When ordering, the following information must be provided to properly size the metering and DC control voltage for your application.

Generator — KW — Voltage — Frequency — Phase — Wire
 Engine — Make — Model No. — Battery Voltage

CONTROL PANEL DIMENSIONS



OPTIONAL EQUIPMENT

1. Emergency stop button (red mushroom knob).
2. Alarm buzzer with silencing switch.
3. Auxiliary relay for dry contacts (2 max.).
- *4. Low water level shutdown.
5. Panel lights with switch.

* Low water level shutdown is paralleled with High Engine Temperature Light on Control Panel.

Katolight will custom-build control panels for applications requiring features not found in the Standard Control Panel. For more information consult the factory.

Materials and Specifications May Change Without Notice.



Printed in U.S.A.

KATOLIGHT CORPORATION

3201 Third Avenue P.O. Box 3229 Mankato, Minnesota 56002-3229

Phone: (507) 625-7973 Telex: 29-0787 FAX: (507) 625-2968