



Shell Fortisol Fleet 15W-40

High quality multi-grade engine oil

Shell Fortisol Fleet 15W-40 is a high quality multi-grade engine oil designed for use in a wide range of highly rated turbocharged and naturally aspirated diesel and gasoline engines.

Shell Fortisol Fleet 15W-40 provides excellent protection in mixed fleet road transport and off highway applications. Extended oil drain intervals may be considered when used in conjunction with our ShellCARE advisory service.

Shell Fortisol Fleet 15W-40 is a blend of highly refined base stock and carefully selected additives to give superior performance in the most powerful high speed diesel engines and in the smaller diesel and gasoline units fitted to light commercial vehicles and passenger cars.

Performance Features

- Piston and piston ring groove cleanliness of a very high order
- Excellent oxidation and thermal stability
- High levels of protection against corrosion and wear
- Effective sludge control

Performance Specifications

Shell Fortisol Fleet 15W-40 is suitable for use where the following specifications are called for;

API Service Classifications CF-4/SG

Health & Safety

Shell Fortisol Fleet 15W-40 is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on product health and safety refer to the appropriate Shell Product Safety Data Sheet. This can be obtained from your own internal Health & Safety focal point. In the event of any queries contact your local Shell Business Development Manager or:

Normal Office Hours
Shell UK Oil Products Ltd
Delta House
Wavell Road
Wythenshawe
Manchester M22 5SB
Tel: 0161 499 4000

Emergencies
Shell UK Oil Products Ltd
Shell Centre
London
SE1 7NA

Tel: 020 7934 1234

Typical Physical Characteristics

SAE Viscosity Grade	15W-40
Kinematic Viscosity	
@ 40 °C cSt	110
@ 100 °C cSt	14.5
(IP 71)	
Viscosity Index	137
(IP 226)	
Density	
@ 15 °C kg/l	0.890
Flash Point °C	
Pensky-Martens Closed Cup	212
(IP 34)	
Pour Point °C	
(IP 15)	-28
Total Base Number	
mg KOH/g	10
(IP 276)	
Sulphated Ash	
% wt	1.3
(IP 163)	

These characteristics are typical of current production. Whilst future production will conform to Shell's specification variations in these characteristics may occur.

Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.