



CUSTOMER APPROVAL SIGNATURE	APPROVAL DATE	COMMENTS
<b>INCLUDED FEATURES</b>		
ENGINE: General Motors 4.3L V-6 (radiator through flywheel)	VABGAC2000	430 Lbs.
ALTERNATOR: MARATHON	36ICSL1600	518 Lbs.
SUB-BASE: STRUCTURAL STEEL	VT087335	292 Lbs.
ISOLATORS: (4) LF2650	VT1F2650	12 Lbs.
SOUND ATTENUATED ENCLOSURE		713 Lbs.
SIDE-IN TOP-OUT VERTICAL MOUNT SILENCER	VT62303	45 Lbs.
OIL DRAIN EXTENSION WITH VALVE ROUTED TO SKID	VT17204N	MISC.
(4) BATTERIES GROUP 31 STYLE 12V BATTERY RACK AND CABLES FOR BATTERY	VT31P6	41 Lbs.
Note: Rack is integral to the skid		MISC.
CONTROL PANEL		MISC.
CIRCUIT BREAKER: AMP ABB		MISC.
ABB ENCLOSURE		MISC.
WEIGHT SUBTOTAL		2,051 Lbs.
MISC. WEIGHT: 5% of subtotal		103 Lbs.
TOTAL WEIGHT:		2,154 Lbs.

ENCLOSURE MATERIAL: 12 & 14 ga. Galvalneal  
 COLOR: AkzoNobel Clay #20-8247HY POWDER COAT

DRAWN	6/13/2011	TITLE	
CHECKED		TAYLOR POWER SYSTEMS	
QA		TG40 Sound Attenuated Enclosure	
MFG		SIZE	DWG NO.
APPROVED		C	TG40 TO TG60 ENC
		SCALE	REV
			SHEET 1 OF 1