

Industrial Tank Heaters

1500-5000 Watt



▶ HIGHLIGHTS

- ◆ Weather Tight
- ◆ Conduit Connection
- ◆ Horizontal or Vertical Mounting
- ◆ Single Phase



▶ SPECIFICATIONS

Ambient Above -20° F	Ambient Below -20° F	Model Number without Thermostat	Model Number with Thermostat (see chart 1)	Volts	Phase	Watts	Amps
350 — 500 Cubic Inch or Less	200 — 300 Cubic Inch or Less	CB115100-000	CB1151XX-000	120	1	1500	12.5
		CB115800-000	CB1158XX-000	208	1	1500	7.2
		CB115200-000	CB1152XX-000	240	1	1500	6.3
		CB115700-000	CB1157XX-000	277	1	1500	5.4
		CB115300-000	CB1153XX-000	380	1	1500	3.9
		CB115400-000	CB1154XX-000	480	1	1500	3.1
500 — 600 Cubic Inch or Less	300 — 400 Cubic Inch or Less	CB120100-000	CB1201XX-000	120	1	2000	16.7
		CB120800-000	CB1208XX-000	208	1	2000	9.6
		CB120200-000	CB1202XX-000	240	1	2000	8.3
		CB120300-000	CB1203XX-000	380	1	2000	5.3
		CB120400-000	CB1204XX-000	480	1	2000	4.2
600 — 800 Cubic Inch or Less	400 — 500 Cubic Inch or Less	CB125100-000	CB1251XX-000	120	1	2500	20.8
		CB125800-000	CB1258XX-000	208	1	2500	12.0
		CB125200-000	CB1252XX-000	240	1	2500	10.4
		CB125700-000	CB1257XX-000	277	1	2500	9.0
		CB125300-000	CB1253XX-000	380	1	2500	6.6
		CB125400-000	CB1254XX-000	480	1	2500	5.2
800 — 1000 Cubic Inch or Less	500 — 600 Cubic Inch or Less	CL130100-100	CL1301XX-100	120	1	3000	25.0
		CL130800-100	CL1308XX-100	208	1	3000	14.4
		CL130200-100	CL1302XX-100	240	1	3000	12.5
		CL130700-100	CL1307XX-100	277	1	3000	10.8
		CL130300-100	CL1303XX-100	380	1	3000	7.9
		CL130400-100	CL1304XX-100	480	1	3000	6.3
1000 — 1350 Cubic Inch or Less	600 — 800 Cubic Inch or Less	CL140800-100	CL1408XX-100	208	1	4000	19.2
		CL140200-100	CL1402XX-100	240	1	4000	16.7
		CL140700-100	CL1407XX-100	277	1	4000	14.4
		CL140300-100	CL1403XX-100	380	1	4000	10.5
		CL140400-100	CL1404XX-100	480	1	4000	8.3
1350 — 1650 Cubic Inch or Less	800 — 1000 Cubic Inch or Less	CL150800-100	CL1508XX-100	208	1	5000	24.0
		CL150200-100	CL1502XX-100	240	1	5000	20.8
		CL150700-100	CL1507XX-100	277	1	5000	18.1
		CL150300-100	CL1503XX-100	380	1	5000	13.2
		CL150400-100	CL1504XX-100	480	1	5000	10.4