

Industrial Tank Heaters

1500-5000 Watt



▶ HIGHLIGHTS

- ◆ Weather Tight
- ◆ Conduit Connection
- ◆ Horizontal or Vertical Mounting
- ◆ Single Phase



▶ SPECIFICATIONS

| Ambient Above -20° F | Ambient Below -20° F | Model Number without Thermostat | Model Number with Thermostat (see chart 1) | Volts | Phase | Watts | Amps |
|--------------------------------|-------------------------------|---------------------------------|--|-------|-------|-------|------|
| 350 — 500 Cubic Inch or Less | 200 — 300 Cubic Inch or Less | CB115100-000 | CB1151XX-000 | 120 | 1 | 1500 | 12.5 |
| | | CB115800-000 | CB1158XX-000 | 208 | 1 | 1500 | 7.2 |
| | | CB115200-000 | CB1152XX-000 | 240 | 1 | 1500 | 6.3 |
| | | CB115700-000 | CB1157XX-000 | 277 | 1 | 1500 | 5.4 |
| | | CB115300-000 | CB1153XX-000 | 380 | 1 | 1500 | 3.9 |
| | | CB115400-000 | CB1154XX-000 | 480 | 1 | 1500 | 3.1 |
| 500 — 600 Cubic Inch or Less | 300 — 400 Cubic Inch or Less | CB120100-000 | CB1201XX-000 | 120 | 1 | 2000 | 16.7 |
| | | CB120800-000 | CB1208XX-000 | 208 | 1 | 2000 | 9.6 |
| | | CB120200-000 | CB1202XX-000 | 240 | 1 | 2000 | 8.3 |
| | | CB120300-000 | CB1203XX-000 | 380 | 1 | 2000 | 5.3 |
| | | CB120400-000 | CB1204XX-000 | 480 | 1 | 2000 | 4.2 |
| 600 — 800 Cubic Inch or Less | 400 — 500 Cubic Inch or Less | CB125100-000 | CB1251XX-000 | 120 | 1 | 2500 | 20.8 |
| | | CB125800-000 | CB1258XX-000 | 208 | 1 | 2500 | 12.0 |
| | | CB125200-000 | CB1252XX-000 | 240 | 1 | 2500 | 10.4 |
| | | CB125700-000 | CB1257XX-000 | 277 | 1 | 2500 | 9.0 |
| | | CB125300-000 | CB1253XX-000 | 380 | 1 | 2500 | 6.6 |
| | | CB125400-000 | CB1254XX-000 | 480 | 1 | 2500 | 5.2 |
| 800 — 1000 Cubic Inch or Less | 500 — 600 Cubic Inch or Less | CL130100-100 | CL1301XX-100 | 120 | 1 | 3000 | 25.0 |
| | | CL130800-100 | CL1308XX-100 | 208 | 1 | 3000 | 14.4 |
| | | CL130200-100 | CL1302XX-100 | 240 | 1 | 3000 | 12.5 |
| | | CL130700-100 | CL1307XX-100 | 277 | 1 | 3000 | 10.8 |
| | | CL130300-100 | CL1303XX-100 | 380 | 1 | 3000 | 7.9 |
| | | CL130400-100 | CL1304XX-100 | 480 | 1 | 3000 | 6.3 |
| 1000 — 1350 Cubic Inch or Less | 600 — 800 Cubic Inch or Less | CL140800-100 | CL1408XX-100 | 208 | 1 | 4000 | 19.2 |
| | | CL140200-100 | CL1402XX-100 | 240 | 1 | 4000 | 16.7 |
| | | CL140700-100 | CL1407XX-100 | 277 | 1 | 4000 | 14.4 |
| | | CL140300-100 | CL1403XX-100 | 380 | 1 | 4000 | 10.5 |
| | | CL140400-100 | CL1404XX-100 | 480 | 1 | 4000 | 8.3 |
| 1350 — 1650 Cubic Inch or Less | 800 — 1000 Cubic Inch or Less | CL150800-100 | CL1508XX-100 | 208 | 1 | 5000 | 24.0 |
| | | CL150200-100 | CL1502XX-100 | 240 | 1 | 5000 | 20.8 |
| | | CL150700-100 | CL1507XX-100 | 277 | 1 | 5000 | 18.1 |
| | | CL150300-100 | CL1503XX-100 | 380 | 1 | 5000 | 13.2 |
| | | CL150400-100 | CL1504XX-100 | 480 | 1 | 5000 | 10.4 |