

## Ratings Range — 60 Hertz Operation

Standby: kW 600  
 kVA 750  
 Prime: kW 540  
 kVA 675

Throughout its 80 year history, **Taylor Machine Works**, which manufactures heavy machinery for industries worldwide, has maintained a reputation of having unparalleled products with service to match. **Taylor Power Systems** is no different!

In the early 1980's Taylor Machine Works created Taylor Power Systems to distribute industrial engines and manufacture generator sets offering diesel powered 9 kW to 2000 kW and gaseous powered 30 kW to 400 kW. Taylor Power Systems provides quality standby and prime generator sets in stationary or mobile configurations for a wide variety of applications for example the Healthcare and Telecommunications Industries, Public Utilities, Federal, State and Local Government agencies, Educational and Financial Institutions as well as Agricultural.

Taylor Power Systems is your 21st Century Power Source!

- Single source responsibility for the generator set and accessories.
- Prototype and production tested to insure one step load acceptance per NFPA 110.
- Two year limited warranty on generator sets and accessories. Extended warranties also available.
- Unit conforms to CSA, NEMA, EGSA, ANSI and other standards.
- Heavy duty 4 cycle industrial engine for reliability and fuel efficiency.
- Brushless rotating field generator with class H insulation.
- Heavy duty steel base with integral vibration isolators.
- Cooling system designed for ambient temperatures up to 50°C (122°F)
- EPA Tier 3 Certified Engine.
- Tier 3 EPA-Certified for Stationary Emergency Applications.


## Genset Ratings

Genset Model Number	Alternator	Voltage L-N / L-L	Phase	Hertz	130° Rise Standby Rating		105° Rise Prime Rating	
					kW / kVA	Amps	kW / kVA	Amps
TMC600	573RSL4033	277/480	3	60	600/750	902	540/675	811
		139/240	3	60	600/750	1804	540/675	1624
		254/440	3	60	600/750	984	540/675	886
		127/220	3	60	600/750	1968	540/675	1771
		240/416	3	60	600/750	1040	540/675	937
		120/208	3	60	600/750	2081	540/675	1874
		120/240	3	60	600/750	1804	540/675	1624
		219/380	3	60	595/744	1130	535/669	1016
		120/240	1	60	385/385	1604	346/346	1441

RATINGS: All three-phase units are rated at 0.8 power factor. All single-phase units are rated at 1.0 power factor.  
 STANDBY RATINGS: Standby ratings apply to installations served by a reliable utility source. The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Ratings are in accordance with ISO-3046/1, BS 5514, AS 2789, and DIN 6271.  
 PRIME POWER RATINGS: Prime power ratings apply to installations where utility power is unavailable or unreliable. At varying load the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve. Ratings are in accordance with ISO-8528/1, overload power in accordance with ISO-3046/1, BS5514, AS2789, and DIN 6271. For limited running time and base load ratings consult the factory. The generator set manufacturer reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever.  
 GENERAL GUIDELINES FOR DERATION: Altitude: Derate 0.5% per 100m (328 ft.) elevation above 1000m (3279 ft.) Temperature: Derate 1.0% per 10°C (18°F) temperature above 40°C (104°F).




# Generator Controller Options



## Digital Control Panel

- Integrated engine-genset control, protection, and metering
- Microprocessor allows for exact measurement, setpoint adjustment, and timing functions
- Front panel 3 position controls and indicators enable quick and simple operation
- Emergency stop push button and an Alarm Horn with silence button
- A wide temperature-range liquid crystal display (LCD) with backlighting
- SAE J1939 Engine ECU communications
- Multilingual capability
- Remote RS-485 communications for Optional RDP-110 Remote Annunciator
- 4 programmable contact inputs and 10 contact outputs (2 A/c rated)
- Modbus Communications with RS-485, Battery Backup for Real Time Clock, UL recognized, CSA certified, CE approved, HALT (Highly Accelerated Life Tests) tested, IP 54 Front Panel rating with integrated gasket. and NFPA 110 Level 1 Compatible.



## Analog Controller

- Analog instruments to monitor AC voltage, AC frequency, oil pressure, water temperature, battery voltage, fuel level, run time/hour meter and percent of load
- Red LED indication for overspeed, overcrank, low oil pressure, and high coolant temperature
- Green LED indication of engine running
- Control switch is provided for local and remote starting with 3 position run/off/remote switch
- Engine mounted emergency by-pass key switch

# Alternator Specifications

<p><b>Manufacturer</b> Marathon</p> <p><b>Type</b> Ext. Voltage Regulated, Brushless</p> <p><b>Gen Frame</b> MAGNAPLUS</p> <p><b>Insulation</b> NEMA</p> <p><b>Material</b> Class H</p> <p><b>Temperature Rise</b> 130 °C, Standby</p> <p><b>Hertz</b> 60</p> <p><b>Phase</b> 3</p> <p><b>RPM</b> 1800</p> <p><b>Exciter</b> Rotating</p> <p><b># Leads</b> 12 Reconnectable or 4 Single Phase</p> <p><b>PF</b> 0.8</p> <p><b>Ambient</b> 40°C</p> <p><b>Coupling Single Bearing</b> Flexible</p> <p><b>Amortisseur Windings</b> Full</p> <p><b>Cooling Air Volume</b> 250 CFM</p> <p><b>Peak Motor Starting</b> 30% Voltage Dip, 850 kVA</p> <p><b>Voltage Regulation</b> 1 Phase Sensing 1%</p> <p><b>no-load and full-load</b> Optional 3 Phase Sensing 1/2%</p>	<ul style="list-style-type: none"> <li>• NEMA MG1, IEEE, AND ANSI standards compliance for temperature and motor starting.</li> <li>• Sustained short-circuit current of the rated current for up to 10 seconds.</li> <li>• Sustained short-circuit current enabling downstream circuit breakers to trip without collapsing the alternator field.</li> <li>• Self-ventilated and dripproof construction.</li> <li>• Superior voltage waveform from a two-thirds pitch stator and skewed rotor.</li> <li>• Linkboards</li> <li>• Optimized Electrical Design</li> <li>• Enhanced Ventilation</li> <li>• Fully Guarded</li> <li>• Heavy Duty Bearings</li> <li>• Design Specs and Agency Approvals</li> </ul>
---	---

## STANDARD FEATURES

- Trailer with integral fuel tank
- Vibration Isolators
- Oil Drain Valve with Extension
- Battery
- Battery Rack
- Battery Cables
- Water jacket heater
- Flexible Fuel Lines
- High Ambient Unit Mounted Radiator
- Battery Charging Alternator
- Factory Paint
- Factory Test Prior to Shipment
- 2 Year Warranty
- Owners Manual

## AVAILABLE ACCESSORIES

### ENCLOSED UNIT

- Standard Enclosure With Internal Silencer
- Sound Attenuated Enclosure With Silencer

### CONTROLLER

- DGC2020 Control Panel
- DGC2020 Control Panel with Modem
- DGC2020 with Generator Protection
- DGC2020 with Modem and Generator Protection
- Flush or Surface Mount Remote Annunciator
- Remote Mount Break Glass E-Stop Switch
- Analog Control Panel

### MISCELLANEOUS

- Coolant Drain Kit
- Water Jacket Heater
- Oil Pan Heater
- Generator Strip Heater
- Battery Charger
- Pad Type Battery Heater
- Battery Heater Blanket with Thermostat

- Line Circuit Breaker
- Output Power Cable
- Y-YY-ZZ Multi-voltage selector switch
- 20 amp 120vac and GFI receptacle
- 20 amp 120vac GFI and 30 amp 120/240vac twist lock receptacle
- 30 amp 120vac RV receptacle
- Cam-Loks
- Diesel Locomotive cable
- Extenda-Lites
- Hydraulic Brake Kit
- Pintle ring hitch
- Spare tire kit
- Lug wrench
- Hydraulic Jack
- Single Point Lift


### WARRANTY

- 3 Year Warranty
- 5 Year Warranty

## WEIGHTS AND DIMENSIONS

OVERALL SIZE, L x W x H: 322 in. x 102 in. x 141 in.  
WEIGHT (DRY): 18960 lbs.

Note: Dim and weights reflect standard open unit with no options



Note: This drawing is provided for reference only and should not be used for planning installation. Contact your local distributor for more detailed information.

## DISTRIBUTED BY: