



CUSTOMER APPROVAL SIGNATURE	APPROVAL DATE	COMMENTS
INCLUDED FEATURES		
ENGINE: Cummins 6387G5 (radiator through flywheel)	06SB7G5	1482 Lbs.
ALTERNATOR: MARATHON	431CSL6206	1415 Lbs.
SUB-BASE: STRUCTURAL STEEL	V708/7422	336 Lbs.
UL142 DOUBLE WALL BASKET/180 gallons	V712/46432	870 Lbs.
STANDARD ENCLOSURE		890 Lbs.
SIDE-IN TOP-OUT VERTICAL MOUNT SILENCER	62304	80 Lbs.
ISOLATORS: (4) E80D 4960060	V74960060	12 Lbs.
FUEL SYSTEM:	V7GRU0310	MISC.
OIL DRAIN EXTENSION: WITH VALVE ROUTED TO SKID	V7T22AN	MISC.
CABLE AND WIRING	N/A	MISC.
HARDWARE (BOLTS, WASHERS, NUTS, & LATCHES)	N/A	MISC.
(3) BATTERIES: GROUP 21 STYLE 12V BATTERY	V731P6	41 Lbs.
BACK PANEL: 12V BATTERY		MISC.
NOTE: Rock is integral to the skid		MISC.
CONTROL PANEL	xxxxx	MISC.
CIRCUIT BREAKER: ABB	xxxxx	MISC.
ABB ENCLOSURE		MISC.
WEIGHT SUBTOTAL		5126 Lbs.
MISC. WEIGHT: 5% of subtotal		256 Lbs.
TOTAL WEIGHT OPEN UNIT:		5382 Lbs.

ENCLOSURE MATERIAL: 14 ga. Galvaneal
 COLOR: AKZONobel Clay #20-8247HY POWDER COAT

DRAWN		6/13/2011	
CHECKED			
QA			
PENG			
APPROVED			
TITLE		TAYLOR POWER SYSTEMS	
Standard Enclosure			
Model TD200 (180 gal. tank)			
SIZE	DWG NO.	REV	
C	TD150		
SCALE	SHEET 1 OF 1		