



CUSTOMER APPROVAL SIGNATURE	APPROVAL DATE	COMMENTS
INCLUDED FEATURES		
ENGINE: Cummins 03B705 (rotator through flywheel)	03B705	1482 Lbs.
ALTERNATOR: MARATHON	43ICSL6206	1415 Lbs.
SUB-BASE STRUCTURAL STEEL	V1087422	336 Lbs.
UL142 DOUBLE WALL BASKET/TANK 600 gallons	V13646132	1675 Lbs.
STANDARD ENCLOSURE		890 Lbs.
SIDE-IN TIP-OUT VERTICAL MOUNT SILENCER	62304	80 Lbs.
ISOLATORS: (4) EBCO 4960060	V14960060	12 Lbs.
FUEL SYSTEM	V16R00310	MISC.
DIL DRAIN EXTENSION WITH VALVE ROUTED TO SKID	V17204N	MISC.
CABLE AND WIRING	N/A	MISC.
HARDWARE (BOLTS, WASHERS, HINGES, & LATCHES)	N/A	MISC.
(3) BATTERIES: GROUP 31 STYLE 12V BATTERY RACK AND CABLES FOR BATTERY	V13P6	41 Lbs.
Note: Rack is integral to the skid		
CONTROL PANEL		MISC.
CIRCUIT BREAKER: ABB	xxxxx	MISC.
ABB ENCLOSURE	xxxxx	MISC.
WEIGHT SUBTOTAL		5931 Lbs.
MISC. WEIGHT 5% of subtotal		297 Lbs.
TOTAL WEIGHT OPEN UNIT:		6228 Lbs.

ENCLOSURE MATERIAL: 14 ga. Galvaneal
 COLOR: Akzonobel Clay #20-8247HY POWDER COAT

PROGRAM	DATE	BY	REVISION
	6/13/2011		
APPROVED			
QA			
DESIGN			
TAYLOR POWER SYSTEMS			
Standard Enclosure			
Model TD200 (600 gal. tank)			
SIZE	DWG NO.	REV	
C	TDJ150		
SCALE			
SHEET 1 OF 1			