



CUSTOMER APPROVAL SIGNATURE	APPROVAL DATE	COMMENTS
INCLUDED FEATURES		
ENGINE: PERKINS 2206D-E13TA2 Electropak (radiator through flywheel)	VAE13TA22	3,298 Lbs.
ALTERNATOR: Marathon	432S3L212	1,760 Lbs.
SUB-BASE: STRUCTURAL STEEL	VT087522	780 Lbs.
SKID EXTENSION	VT087523	327 Lbs.
UL142 DBL WALL BASKETANK	500 GALLON	2560 Lbs. dry
ISOLATORS: (2) LF42100	VTLE31200 VTLEF42100	12 Lbs. 15 Lbs.
ENCLOSURE: POWDER COAT, 12&14 GA. STEEL SOUND ATTENUATED	VTGR008	1,804 Lbs.
SILENCER: QUIET SHIELD CRITICAL GRADE 6"	VTG2306F	170 Lbs.
FLEX FUEL LINES:	VTGR003125	MSC.
WIRE AND CABLE		MSC.
FLUIDS		MSC.
FLUID DRAIN (ROUTED TO SKID)		MSC.
STAINLESS HARDWARE (BOLTS, HINGES, ETC.)		MSC.
(2) BATTERIES: 80 STLF RACK AND CABLES FOR (2) BATTERIES Note: Rack is integral to the skid	VTB0	150 Lbs.
CONTROL PANEL		MSC.
CIRCUIT BREAKER: ABB		MSC.
WEIGHT SUBTOTAL		10,836 Lbs.
MSC. WEIGHT: 5% of subtotal		542 Lbs.
TOTAL WEIGHT:		11,378 Lbs.

TAYLOR POWER SYSTEMS		SCALE:	DRAWN BY	JMM
PART NAME	TD300 SOUND ATTENUATED ENCLOSURE UNIT WITH 500 GALLON BASKETANK	DATE:	2/2/2012	REVISED
DRAWING NUMBER	MODEL	APPROVED BY		
		CUSTOMER		