



CUSTOMER APPROVAL SIGNATURE	APPROVAL DATE	COMMENTS
INCLUDED FEATURES		
ENGINE: PERKINS 2206D-E13TAC3 Electrolog (radiator through flywheel)	VAE1317A62	3,298 Lbs.
ALTERNATOR: Marathon	433CS16R220	2,245 Lbs.
SUB-BASE: STRUCTURAL STEEL	V10R81522	780 Lbs.
SKID EXTENSION	V10R81523	327 Lbs.
ISOLATORS: (2) LF31200	V1LF31200	12 Lbs.
(2) LF42100	V1LF42100	15 Lbs.
ENCLOSURE: POWDER COAT, 12x14 GA. STEEL STANDARD WEATHER HOUSING	VFRU008	1,804 Lbs.
SILENCER: QUIET SHIELD CRITICAL GRADE 6" INTERNALLY MOUNTED	VFR2306F	170 Lbs.
FLEX FUEL LINES:	VFRU03125	MISC.
WIRE AND CABLE		MISC.
FLUIDS		MISC.
FLUID DRAIN (ROUTED TO SKID)		MISC.
STAINLESS HARDWARE (BOLTS, HINGES, ETC.)		MISC.
(2) BATTERIES: 80 STYLE RACK AND CABLES FOR (2) BATTERIES Note: Rack is integral to the skid CONTROL PANEL	V1B0	150 Lbs.
CIRCUIT BREAKER: ABB		MISC.
WEIGHT SUBTOTAL		8,761 Lbs.
MISC. WEIGH: 5% of subtotal		438 Lbs.
TOTAL WEIGHT:		9,199 Lbs.

TAYLOR POWER SYSTEMS		SCALE:	DRAWN BY
PART NAME	TD400 STANDARD ENCLOSURE	DATE: 6-21-11	JMM
DRAWING NUMBER	MODEL	APPROVED BY	
		CUSTOMER	