



CUSTOMER APPROVAL SIGNATURE		APPROVAL DATE	COMMENTS
INCLUDED FEATURES	PART #	WEIGHT	
ENGINE: PERKINS 2806C-E15TA64 Electropump (optional "through flywheel")	25906C-E15TA64	3,600 Lbs.	
ALTERNATOR: MARATHON	572RSL4031	3110 Lbs.	
SUB-BASE: STRUCTURAL STEEL		1158 Lbs.	
ISOLATORS: (2) LT-3280	VTLF3280	12 Lbs.	
	VTLF42800	13 Lbs.	
ENCLOSURE: CLAY POWDER COAT, 14 GA. STEEL STANDARD WEATHER HOUSING	VTR0008	1777 Lbs.	
SILENCER: SIDE-IN TOP-OUT VERTICAL MOUNT SILENCER INTERNALLY MOUNTED	VTC2306	170 Lbs.	
(2) BATTERIES: 8D STYLE RACK AND CABLES FOR (2) BATTERIES Note: Rack is integral to the shell	VTR0	150 Lbs.	
FLEX FUEL LINES	VTR0003125	MISC.	
WIRE AND CABLE		MISC.	
FLUIDS		MISC.	
STAINLESS HARDWARE (BOLTS, NUTS, ETC)		MISC.	
CONTROL PANEL		MISC.	
WEIGHT SUBTOTAL		9,992 Lbs.	
MISC. WEIGHT 5% of subtotal		500 Lbs.	
TOTAL WEIGHT:		10,492 Lbs.	

ENCLOSURE MATERIAL: 12 & 14 ga. Galvaneal
 COLOR: AkzoNobel Clay #20-8247HY POWDER COAT

DESIGN	6/14/2011	TITLE	
DATE		TAYLOR POWER SYSTEMS	
BY		TD550 STANDARD ENCLOSURE	
CHK		SIZE	DWG NO.
APP		C	TD450 TO TD550 Assembly
REV		SCALE	SHEET 1 OF 1