



CUSTOMER APPROVAL SIGNATURE	APPROVAL DATE	COMMENTS
INCLUDED FEATURES		
ENGINE PERKINS 2806C-E18TA03 Electric (crank through flywheel)	VAE18TA03	4,500 Lbs.
ALTERNATOR MAXATION	5728SL403	3,400 Lbs.
SUB-BASE STRUCTURAL STEEL	V10B7704	909 Lbs.
ENCLOSURE CLAY POWDER COAT, 14 GA. STEEL SOUND ATTENUATED	V10R008	1850 Lbs.
SILENCER, SIDE-IN TOP-OUT VERTICAL MOUNT	V162308	365 Lbs.
500 GALLON U-LINE DOUBLE WALL SUB BASE TANK	U41-8131-MS	2566 Lbs.
ISOLATORS (2) L731200	V1LF31200	12 Lbs.
(4) L742100	V1LF42100	30 Lbs.
FLEX FUEL LINES	V10R002125	MISC.
OIL DRAIN EXTENSION, 1" VALVE IN SKID	V170001	MISC.
(2) BATTERIES 80 STYLE PACK AND CABLES FOR (2) BATTERIES Note: Rack is integral to the skid	V1B180	150 Lbs.
CIRCUIT BREAKER ABB BREAKER ENCLOSURE CONTROL PANEL	XXXX XXXX	MISC. MISC.
WEIGHT SUBTOTAL		13,742 Lbs.
MISC. WEIGHT 5% of subtotal		687 Lbs.
TOTAL WEIGHT		14,429 Lbs.

ENCLOSURE MATERIAL: 12 & 14 ga. Galvalneal
 COLOR: AkzoNobel Clay #20-8247HY POWDER COAT

DATE	01/19/2012	TITLE	TAYLOR POWER SYSTEMS
DRAWN			
CHECKED			
BY			
REV			
APPROVED			
		SIZE	5/8x10
		SCALE	
			457