



CUSTOMER APPROVAL SIGNATURE	APPROVAL DATE	COMMENTS
		<b>INCLUDED FEATURES</b>
		ENGINE: PERKINS 2806C-E18/MA3
		Electro-Mech Governor (through flywheel)
		ALTERNATOR: HAWORTH
		SUB-BASE: STRUCTURAL STEEL
		ENCLOSURE: CLAY POWDER COAT, 14 GA. STEEL
		ENCLOSURE: SOUND ATTENUATED
		STEAMER: 3/8" IN TOP-OUT VERTICAL MOUNT
		975 GALLON UL42 DOUBLE WALL SUB BAKETANK
		ISOLATORS: (2) LF31800
		(4) LF42100
		FLEX FUEL LINES: V176R0325
		OIL DRAIN EXTENSION: 1" VALVE IN SKID
		OIL DRAIN EXTENSION: V172R01
		(2) BATTERIES: 8B STYLE
		(2) BATTERIES: 8B BATTERIES
		Note: Rack is integral to the skid
		CONTROL PANEL
		CIRCUIT BREAKER: ABB BREAKER ENCLOSURE
		WEIGHT SUBTOTAL
		MISC. WEIGHT: 5% of subtotal
		TOTAL WEIGHT:
		4,520 Lbs.
		3,400 Lbs.
		909 Lbs.
		1,850 Lbs.
		305 Lbs.
		3,326 Lbs.
		12 Lbs.
		30 Lbs.
		MISC.
		MISC.
		150 Lbs.
		MISC.
		MISC.
		14,502 Lbs.
		755 Lbs.
		15,227 Lbs.

ENCLOSURE MATERIAL: 12 & 14 ga. Galvaneal  
 COLOR: AkzoNobel Clay #20-8247HY POWDER COAT

DATE	01/19/2012	TITLE	TAYLOR POWER SYSTEMS
DRAWN BY		DATE	
CHECKED BY		SCALE	
QA		SIZE	
PROJ		PROJECT NO.	
DESCRIPTION		REV	