CUSTOMER APPROVAL SIGNATURE	APPROVAL DATE	COMMENTS

INCLUDED FEATURES	PART #	WEIGHT
ENGINE: PERKINS 404D-22TAG (radiator through flywheel)	404D-22TAG	675 Lbs.
ALTERNATOR: MARATHON 283CSL1507	283CSL1507	350 Lbs.
SUB-BASE: STRUCTURAL STEEL	VT087375	126 Lbs.
ISOLATORS: (4) Barry Controls 256416	VT256416	4 Lbs.
ENCLOSURE: CLAY POWDER COAT, 14 GA. STEEL STANDARD ENCLOSURE	VTGRU08459	465 Lbs.
FUEL TANK: UL142 175 GALLON DOUBLE WALL	VT244078	788 Lbs.
SILENCER: SIDE-IN TOP-OUT VERTICAL MOUNT INTERNALLY MOUNTED	VT62302	19 Lbs.
(1) BATTERIES: GROUP 26 STYLE 12V BATTERY RACK AND CABLES FOR BATTERY Note: Rack is integral to the skid	VT6026	30 Lbs.
CIRCUIT BREAKER: ABB BREAKER ABB ENCLOSURE		MISC. MISC.
FUEL LINES/FITTINGS	VTGRU03135	MISC.
FLUID DRAIN EXTENSION: WITH VALVE ROUTED TO SKID	VTF108N	MISC.
CONTROL PANEL		MISC.
HARDWARE: BOLTS, NUTS, WASHERS, LATCHES		MISC.
FLUIDS: OIL& ANTIFREEZE		MISC.
WEIGHT SUBTOTAL		2,457 Lbs.
MISC. WEIGTH 5% of subtotal		123 Lbs.
TOTAL WEIGHT:		2,580 Lbs.











DRAWN: JMM	8-31-11	TAYLOR POWER SYSTEMS
CHECKED		TITLE: TD30 STANDARD ENCLOSURE WITH 175 GALLON BASETANK
QA		
MFG		
APPROVED		SIZE / DWG NO / REV
		SCALE