CUSTOMER APPROVAL SIGNATURE	APPROVAL DATE	COMMENTS

INCLUDED FEATURES	PART #	WEIGHT
ENGINE: PERKINS 403D-11G (radiator through flywheel)	GJ65598	285 Lbs.
ALTERNATOR: MARATHON 281CSL1502	281CSL1502	220 Lbs.
SUB-BASE: STRUCTURAL STEEL	VT087375	126 Lbs.
ISOLATORS: (4) Barry Controls 256416	VT256416	4 Lbs.
ENCLOSURE: CLAY POWDER COAT, 14 GA. STEEL SOUND ATTENUATED ENCLOSURE	VTGRU08459	465 Lbs.
FUEL TANK: UL142 175 GALLON DOUBLE WALL	VT244078	788 Lbs.
SILENCER: SIDE-IN TOP-OUT VERTICAL MOUNT INTERNALLY MOUNTED	VT62302	19 Lbs.
(1) BATTERIES: GROUP 26 STYLE 12V BATTERY RACK AND CABLES FOR BATTERY Note: Rack is integral to the skid	VT6026	30 Lbs.
CIRCUIT BREAKER: AMP ABB ABB ENCLOSURE		MISC. MISC.
FUEL LINES/FITTINGS	VTGRU03135	MISC.
FLUID DRAIN EXTENSION: WITH VALVE ROUTED TO SKID	VTF108N	MISC.
CONTROL PANEL		MISC.
HARDWARE: BOLTS, NUTS, WASHERS, LATCHES		MISC.
FLUIDS: OIL& ANTIFREEZE		MISC.
WEIGHT SUBTOTAL		1,937 Lbs.
MISC. WEIGTH 5% of subtotal		97 Lbs.
TOTAL WEIGHT:		2,034 Lbs.











ENCLOSURE MATERIAL: 14 ga. Galvaneal
COLOR: AkzoNobel Clay #20-8247HY POWDER COAT

DRAWN JMM	8-31-11	TAYLOR POWER SYSTEMS
CHECKED		TITLE: TD9 SOUND ATTENUATED ENCLOSURE WITH 175 GAL BASETANK
QA		
MFG		
APPROVED		SIZE / DWG NO / REV
		SCALE