

Eye Protection: Use of safety glasses with splash guards or full face shield is recommended.

Other protective equipment: Use of solvent resistant or other clothing is recommended.

SECTION 8 - SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled:
Avoid breathing vapors. Ventilate area, remove all sources of ignition, clean up area with absorbent material and place in closed containers for disposal.
Waste Disposal Method: Dispose in accordance with local, state and Federal regulations. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.

*****SECTION 9 SPECIAL PRECAUTIONS*****

Precautions to be taken in handling and storage:
Store and use in a cool, dry, well ventilated area. Do not store above 120° F. Do not puncture or incinerate (burn) cans. Do not stick pin, needle, nail or any other sharp object into opening on top of can. Do not spray into eyes. Do not take internally. See product label for additional information.

Other precautions:
To retard or prevent the release of airborne particulate matter during the use of this product, carefully follow the label for direction and use. Storage should be in areas suitable for Level 3 aerosols.

Date entered: 10-26-92

Date revised: 10-26-92

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgement in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations, or warranties, either express or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, CYCLO Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.

CYCLO INDUSTRIES, INC.
(subsidiary of Accra Pac Group, Inc.)
MATERIAL SAFETY DATA SHEET

1374 North Killian Drive, Suite A, Lake Park, Florida 33403

Phone: 800-843-7813

This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this product. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL, STATE, and COMMUNITY RIGHT TO KNOW regulations. Also make this information available to any employees who requests it.

If CYCLO Industries, Inc. considers the formula of this product to be a trade secret, the exact chemical names of the ingredients(s) and the percentages in which they are combined will not appear in the body of this sheet. The exact composition is available upon request to physicians, industrial hygienists, and other health professionals.

*****SECTION I PRODUCT IDENTIFICATION*****

Product name: CYCLO BRAKE AND PARTS CLEANER (C-111)

Chemical Name: NA

Hazardous Material Description: NA

Chemical Family: NA Formula: BLEND

*****SECTION 2 - PHYSICAL DATA*****

Boiling Point: Not applicable Specific Gravity: NA

Vapor Pressure: NA Vapor Density: NA

Percent Volatile by volume: (%) 100

Solubility in water: Slight pH: NA

Evaporation rate: Slower than ether

Appearance and Odor: Aerosol product; typical solvent odor

*****SECTION 3 HAZARDOUS INGREDIENTS*****

Components	CAS Number	Percent	PEL/TVA
Heptane	142-82-5	51	400 PPM PEL TLV: NA
*Acetone	67-64-1	21	750 PPM PEL 750 PPM TLV
*Toluene	108-88-3	21	200 PPM PEL 100 PPM TLV
Carbon Dioxide	124-38-9	6	10000 PPM PEL 5000 PPM TLV

* Indicates toxic chemicals(s) subject to reporting requirements of Section 313 of Title III and of 40 CFR 372.

*****SECTION 4 FIRE AND EXPLOSION HAZARD DATA*****

Flash point: < 20 ° F Method used: SETAFLASH

Extinguishing Media: Foam, alcohol foam, CO₂, dry chemical, water fog

Special Fire Fighting Equipment:
Water spray may be ineffective, water may be used to cool containers to prevent pressure build up and explosion when exposed to extreme heat. If water is used, fog nozzles preferred. Wear goggles and self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:
Keep containers from heat and open flames. Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Vapor accumulation can flash or explode if ignited. Overexposure to decomposition products may cause a health hazard, symptoms may not be readily apparent. Obtain medical attention.

*****SECTION 5 HEALTH HAZARD DATA*****

EFFECTS OF OVEREXPOSURE

Ingestion:
Can cause gastro-intestinal irritation, vomiting, diarrhea, and death. If swallowed, call a physician immediately.

Inhalation:
Respiratory irritation, headache, nausea, fatigue, drowsiness, impaired co-ordination, possible unconsciousness. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Skin Contact:
May be absorbed, solvent action can dry and defat the skin causing skin to crack, leading to dermatitis.

Eye Contact:
Liquid or vapors can cause severe irritation, redness, tearing, and blurred

vision; prolonged contact may lead to corneal damage.

Acute:
Eye irritant, skin irritant, narcotic in high concentrations.
Chronic:
Unknown for product as a whole.

FIRST AID PROCEDURES:

Ingestion:
Call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Skin Contact:
Wipe off with a towel, wash with soap and water. Get medical attention if irritation persists.

Inhalation:
Remove to fresh air, administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

Eye Contact:
Wash immediately with large volumes of fresh water for at least fifteen minutes. Get medical attention.

*****SECTION 6 REACTIVITY DATA*****

Stability: Stable

Conditions to Avoid:
Application to hot surfaces, storage above 120° F exposure to open flame.

Incompatibility: (Materials to avoid) Strong oxidizing agents.

Hazard Decomposition Products: May produce fumes when heated to decomposition. Fumes may contain carbon monoxide, and other toxic fumes.

Hazardous Polymerization: Will not occur.

*****SECTION 7 SPECIAL PROTECTION INFORMATION*****

Respiratory Protection: Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination of particles and vapor. In confined areas, use approved air line type respirators or hoods. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Ventilation: Sufficient to prevent inhalation of solvent vapors. General dilution and/or local exhaust ventilation in volume or pattern to keep PEL/TLV of most hazardous ingredients below acceptable limits and LEL below stated limit.

Protective Gloves: Solvent resistant required for prolonged or repeated contact.